## **EUROPEAN PATENT OFFICE**

## Patent Abstracts of Japan

**PUBLICATION NUMBER** 

07165455

**PUBLICATION DATE** 

27-06-95

APPLICATION DATE

12-09-94

APPLICATION NUMBER

06217015

APPLICANT: SEKISUI CHEM CO LTD;

INVENTOR :

KAMIYA MASATAKE;

INT:CL

C04B 28/26 C04B 7/26 C04B 7/32 C04B 12/04 //(C04B 28/26 , C04B 22:06

C04B 18:08 , C04B 22:08 , C04B 14:10 ) C04B111:28

**CURABLE INORGANIC COMPOSITION** 

PURPOSE: To obtain a curable inorganic composition having high strength and excellent durability such as heat-resistance and weather resistance in a short time by compounding prescribed reactive inorganic powder with an alkali metal slicate and water.

CONSTITUTION: This curable inorganic composition is produced by compounding (A) 100 pts.wt. of reactive inorganic powder obtained by compounding (a) 20-99.5wt.% of one or more kinds of inorganic powder selected from fly ash containing >80wt.% of powder having particle diameter of ≤20µm, fly ash baked at 400-1000°C and containing ≥80wt,% of powder having particle diameter of ≤20µm and inorganic powder produced by applying mechanical energy of 0.1-30Kwh/kg to clay with (b) 0.5-80wt.% of one or more kinds of alumina powder selected from alumina cement powder, y-alumina powder and alumina powder produced by flame-spraying with (B) 1-300 pts.wt. of an alkali metal silicate and (C) 10-1,000 pts.wt. of water.

COPYRIGHT: (C)1995,JPO